



5" Rebounding Steel Bollard

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS5Y-42-RB**



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	5.56" (5" ANSI Schedule 40)
Product Weight	110 lb.
Product Height	42" overall
Impact Rating	I12-5 (13,600 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Set Screws	Six (6) M16
Anchor Screws	Six (6) 5/8" x 5-1/2" Concrete
Cap	Metal, RAL 1023 Yellow

Recommended Uses

- Medium to heavy duty
- Where forks or cantilevers typically shear bolts
- Interior dock doors, corners, rollup doors, fire risers, & internal access doors
- Exterior signpost
- Equipment and storage rack guarding
- Pedestrian safety
- Access denial
- Utility protection
- Pre- and post-tensioned concrete capable
- Internal use where forks have speed
- Not for K-Rated security use

Impact Chart

Impact Angle	90°
Rating	13,600 joules
ANSI MH 31.2	I12-5
Mass (lbs)	Speed (mph)
5,000	7.7
7,500	6.3
10,000	5.5
12,500	4.9
15,000	4.5
17,500	4.1
20,000	3.9
25,000	3.5
30,000	3.2

4955 Stout Drive, San Antonio, TX 78219
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com
 January 2024

