




IronFlex Column Protectors Type 2

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N SS-T2Y-XX-CP



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Cap	Black Plastic
Impact Rating	33.300 joules/250.8kN
Anchors	(16) M16x140 concrete

Recommended Uses

Protects from impact to building structures
Guard columns and other vertical members

Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	33.300	66.620 calculated	133.200 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
3,000	17.0	24.0	33.9
4,000	14.7	20.8	29.4
5,000	13.1	18.6	26.3
6,000	12.0	17.0	24.0
7,000	11.1	15.7	22.2
8,000	10.4	14.7	20.8
9,000	9.8	13.9	19.6
10,000	9.3	13.1	18.6
15,000	7.6	10.7	15.2

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com
January 2024

