



Rebounding Steel Bollard Type 2

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS-T2Y-100**



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	101,6 mm (6,3 mm wall)
Height	100 cm
Impact Rating	10.200 joules, 62,7kN
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Base Coating	Environmentally Friendly Water-based KTL Coating + Polyester Powder Coat C51 corrosion resistance
Set Screws	5m 16 x 2,00, 8 mm Hex
Anchor Screws	Four (4) M16x140 Concrete
Cap	Black Plastic

Recommended Uses

- Medium duty guarding
- Door and wall protection
- Fuel and parking facilities
- Utility protection
- Pedestrian safety
- Access denial
- Fuel pump protection
- Not for hostile vehicle security

Impact Chart

Impact Angle	90°
Rating	10.200 joules
Mass (kg)	Speed (kph)
3,000	9.4
4,000	8.1
5,000	7.3
6,000	6.6
7,000	6.1
8,000	5.7
9,000	5.4
10,000	5.1
15,000	4.2

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com

impactrecovery.com

January 2024



©2024 Impact Recovery Systems, Inc.® All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.® SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®

The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691 | D937,700 | D620,823 | D620,824 | D620,825 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.