



Rebounding Steel Bollard Type 2.5

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS-T2.5Y-100**



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	139,7 mm (6,3 mm wall)
Height	100 cm
Impact Rating	13.600 joules, 100kN
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Base Coating	Environmentally Friendly Water-based KTL Coating + Polyester Powder Coat C51 corrosion resistance
Set Screws	6 M16 x 2,00, 8 mm Hex
Anchor Screws	6 M16x140 Concrete
Cap	Black Plastic

Recommended Uses

Medium duty guarding
Door and wall protection
Parking facilities
Fuel and utility protection
Pedestrian safety
Access denial fuel pump protection
Not for hostile vehicle security

Impact Chart

Impact Angle	90°
Rating	13.600 joules
Mass (kg)	Speed (kph)
3,000	10.8
4,000	9.4
5,000	8.4
6,000	7.7
7,000	7.1
8,000	6.6
9,000	6.3
10,000	5.9
15,000	4.8

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com

impactrecovery.com

January 2024



©2024 Impact Recovery Systems, Inc.® All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.® SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®

The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691 | D937,700 | D620,823 | D620,824 | D620,825 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.