



FlexRail Composite Double Guardrail Type 1

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS-T1Y-100-GR2**



Product Specifications

Color	RAL 1023 Yellow
Material	Proprietary Composite
Dimensions	100 cm (customizable) x 2m per section
Rail Break Strength	110 kN
Impact Rating	Rail 10.200 joules Post 7.000 joules
Temperature Rating	5°C to 65°C
Flexible	No Bending Equipment Required for Curves
End Caps	Option Universal End Cap (75 mm overhang)

Recommended Uses

- Light duty
- Industrial equipment protection
- Pedestrian aisle ways
- Utility guarding
- Access denial
- Office protection
- Computer desks and terminals
- Parking perimeters

Rail Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	10.200	20.406 calculated	40.800 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
500	23.0	32.5	46.0
1,000	16.3	23.0	32.5
1,500	13.3	18.8	26.6
2,000	11.5	16.3	23.0
3,000	9.4	13.3	18.8
4,000	8.1	11.5	16.3
5,000	7.3	10.3	14.5
6,000	6.6	9.4	13.3
7,500	5.9	8.4	11.9

Post Impact Chart

Impact Angle	90°
Rating (joules)	7.000
Mass (kg)	Speed (kph)
500	19.0
1,000	13.5
1,500	11.0
2,000	9.5
3,000	7.8
4,000	6.7
5,000	6.0
6,000	5.5
7,500	4.9

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com

impactrecovery.com

March 2024



©2024 Impact Recovery Systems, Inc.® All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.® SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®

The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691 | D937,700 | D620,823 | D620,824 | D620,825 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.